

PRO ADVANTAGE

Pro Advantage Passenger Car Motor Oil

PRO ADVANTAGE SYNTHETIC BLEND PASSENGER CAR MOTOR OILS use state-of-the-art formulations to meet or exceed the demands placed on today's turbocharged and naturally aspirated gasoline, propane, and natural gas engines in passenger cars and light duty trucks. SAE 5W-20 and 5W-30 are Resource Conserving motor oils that exceed API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL, and previous ILSAC categories.

PRO ADVANTAGE OILS are formulated with high-quality, High viscosity index base oils and the necessary performance additives to exceed required specifications.

TYPICAL PROPERTIES			
PERFORMANCE PLUS®	SAE	5W-20	5W-30
API Service		SN	SN
ILSAC		GF-5	GF-5
Kinematic Viscosity			
cSt @ 40° C		50.0	62.1
cSt @ 100° C		8.6	10.4
Viscosity Index		150	157
CCS Viscosity			
cP @ -30° C		6000	6300
cP @ -25° C		-	-
Evaporative Loss, NOACK, wt%		<15	<15
Specific Gravity 15° C		0.862	0.861
Flash Point, °C		218	220
Pour Point, °C		-39	-39
Color (ASTM)		3.0	3.0
Sulfated Ash, wt%		0.92	0.92

NOTE: Values shown above are representative of current production and may vary within modest ranges.



RAINBO OIL COMPANY

Driving Performance Every Day

CUSTOMER SERVICE

800-942-4425 • Dubuque, IA

800-955-6451 • Rockford, IL

800-553-5661 • Burlington, Houghton & Palmyra

www.rainbolubes.com