

Product Data Sheet

DESCRIPTION

Pro Performance Multi-Vehicle ATF is a full synthetic transmission fluid specifically designed for today's technologically enhanced automatic transmissions. Including those requiring GM DEXRON®-VI, Ford Mercon®-V, Mercon®-SP & Mercon®-LV, Chrysler ATF+3 & ATF +4, Toyota T-II, T-III, T-IV & WS, Honda, Acura, Volvo, Mercedes, BMW. It is recommended for use in several heavy-duty automatic transmissions. And backward compatible for use in transmissions previously serviceable by GM DEXRON®-II or DEXRON®-III and Ford Mercon® among others.

Formulated with synthetic base stocks, friction modifiers, seal conditioners, shear stable viscosity modifiers, anti-wear additives and additional components. Pro Performance Multi-Vehicle ATF's advanced technology delivers ultimate protection and peak performance against shudder, slippage, leaks and gear wear commonly associated with transmission degradation.

PERFORMANCE BENEFITS

One fluid for virtually every worldwide transmission application

- Reduces transmission fluid inventory.
- Prevents misapplication and expensive claims.
- Eliminates the need for converters.
- Highly shear stable and improved wear protection
- Superior anti-shudder performance
- Excellent flow properties at low temperatures and film protection at high temperatures
- Extended life of service and performance
-

RECOMMENDED PERFORMANCE SPECIFICATIONS

Please consult application chart for full list of applications. Not recommended for use in continuously variable transmissions (CVT), dual clutch transmissions (DCT), or applications where Ford Type F fluids are recommended. Refer to owner's manual for manufacturer's recommendation.

TYPICAL CHARACTERISTICS

Characteristic	Test Method ASTM-D	
Specific Gravity @ 60F	1298	32
Appearance	Visual	Red
Flash Point, C / F	92	204/400
Pour Point C / F	97	-45 /-49
Viscosity @ 40 C, cSt	445	34.0
Viscosity @ 100 C, cSt	445	-36
Viscosity Index	2270	6
Brookfield Viscosity cP @ -40C	2983	12,500

Plymouth Lubricants

Sheboygan, WI 53081 920-694-0289
www.PlymouthLubricants.com

Product Data Sheet

ATF Type A	Suffix A			
Aisin Warner	M315 Types A-1, AW-1 3309	Lexus	AF3	DEXRON III
			TIV	Toyota Type T, T-II, T-III, T-IV
			WS	Toyota Type WS
Acura	DEXRON II	MAN		339A, F, V1, V2, Z1, Z2, Z3
	Honda ATF-Z1			DEXRON III, MERCON
	ATF DW1			ATF M-V
Alfa Romeo	All vehicles*	Mazda	AF3, MA	MERCON V
Allison	C-3, C-4, TES-389, TES-295*		SLF	MERCON LV
American Motors	ATF +3 (MS7176E)		MLV	Toyota Type T-IV
	ATF +4 (MS 9602)		TIV	DEXRON III (236.9, 236.1) DEXRON II (236.6, 236.7, 236.8)
	LT 71141		AF3	ATF 3403 M115, 236.10
	DEXRON II		SLF	236.12 (NAG1, NAG2)
	G-052-025-A2			236.81
	G-052-162-A1, A2			236.5 (C-4)
	G-052-182-A2			236.2 (Type A)
	G-055-025-A2			236.36 (PSF)
	ZF 5HP19FL, 5HP25A			ZF 4HP20
	TL 52162			
	Toyota WS	Mini Cooper	TIV	Toyota Type T-IV
	DEXRON III		AF2	DEXRON II
	83 22 9 407 (765, 807, 858, 859), LT 71141		AF3	DEXRON III
	83 22 9 400 (272, 275)	Mitsubishi	SLF	DIAMOND SP-II, SP-III, SP-IV
	83 220 397 (114)			Dia Queen J2
	ZF 5HP (18FL, 19FL, 24A, 30)			Nissan ATF
	LA2634	Nissan	SLF	Matic-D, -J, -K, -S
	ETL-7045E	Opel		19 40 700, 19 40 707, 19 40 767
	ETL-8072B	Peugot		ZF 4HP20
	N402			ZF 5HP19FL
	DEXRON VI			Porsche P/N 999 917 547 00 (A2) or 000 043 205 09
	Power Shift TO-2	Porsche	AE	000 043 204 41, ATF 3403-M115
	ATF +3 (MS7176E)		SLF	00004320528, T-IV
	ATF +4 (MS 9602)	Renault	TIV	All vehicles*
	DIAMOND SP-III		AF3	DEXRON III
	Mopar AS68RC		AF6	DEXRON VI
	DEXRON VI		TIV	Toyota Type T-IV
	LT 71141	SAAB	SLF	3309
	ALUMIX MULTI			Aporoil ATF HP
	LT 71141			93 165 146
	Type T-IV			93 165 147*
	MERCON (MS06050501)		AF3	DEXRON III
	MERCON V (XP-5-QM)		AF6	DEXRON VI
	MERCON SP (XT-6-QSP)		TIV	Toyota Type T-IV
	MERCON LV (XT-10-QLV)		SLF	Honda ZF-1
	WSS-M2C-33-A/B/C/D/F/G		TIV	Toyota Type T-IV
	WSS-M2C-138-CJ, 166-H, 185-A, 195-A, 202-B, 910-A, 922-A1, 924-A (XT-8-QAW)		WS	Toyota Type WS
	DEXRON II	Shell		3403, 3353, LA 2634, M-1375.4
	DEXRON III		AF3	DEXRON III
	DEXRON VI		SLF	Subaru ATF
	GM 9986195			Subaru AT-HP
	GM 12378515			DEXRON III
	GM Transfer Case 12378396			DEXRON VI
	GM Transfer Case 12378508			Toyota Type-IV
	DEXRON II		AE	LT 71141
	Honda ATF-Z1		SLF	Nissan Matic S or J
	Honda ATF-DW1			3309, 3317
	SP-II, SP-III, SP-IV			ETL-7045E, ETL-8072B, N402
	NWS-9638			DEXRON III
	Shell M-1375.4			Toyota Type T, T-II, T-III, T-IV
	ATF Red-1K			Toyota Type WS
	Toyota T-IV			M-2950-S, I-286-S
	Toyota WS			G607 (55.6335.XX)
	K17, Jatco 3100 PL085			G1363 (55.3636.XX)
	Matic-D, -J, -K, -S			Turbo, ZF, Ecomat
	DEXRON III		AE	LT 71141
	DEXRON III		SLF	5HP19FL, 5HP24A
	LT 71141, JUM 20238			TL 52162 (This fluid is yellow)
	M-1375.4			G-052-025-A2
	ATF 3403 M115			G-055-025-A2
	ZF 5HP24			G-052-162-A1, A2
	K17, Jatco 3100 PL085			G-052-182-A2
	MERCON V			G-052-990-A2
	M315 Type A-1			Toyota Type-IV
	MERCON			DEXRON/MERCON
	ATF +3			97340, 97341, 1161521, 1161540
	ATF +4			Toyota Type-IV
	ATF 3403 M115			Ecomat ZF TE-ML 02F, 03D, 04D, 05L, 09, 11B
	3309			ZF TE-ML 14 A, B, C, 16L, 17C
	DEXRON III			
	ATF Red-1K			
	M-1375.4			
	Kia SP-II, SP-III, SP-IV			

*Note: PureSYN Multi-Vehicle ATF is not recommended for use in extended drain heavy-duty, Continuously Variable Transmissions (CVT), Dual Clutch Transmissions (DCT) or Type F. Always refer to owners manual for proper fluid recommendation.