

Product Data Sheet

DESCRIPTION

Pro Performance Synthetic dexos1 Gen 2 Motor Oil is formulated with select synthetic base oils and a state-of-the-art additive system to deliver trusted engine protection and peak vehicle performance. Synthetic dexos® Motor Oil provides added resistance to sludge formation and varnish deposits during top-and-go driving and maintains outstanding wear protection under severe driving conditions. Pro Performance Synthetic dexos® Motor Oil is available in SAE grades 0W-20 and 5W-30 and exceeds new car warranty requirements as defined by ILSAC standard GF-6A, API classification Resource Conserving SP and approved and licensed for General Motors dexos1 Gen 2 specification.

PERFORMANCE BENEFITS

- Special chemistry minimizes low speed pre-ignition. (LSPI)
- Excellent wear protection for critical engine components.
- Ultimate low-temperature engine protection and performance.
- Maintains maximum engine protection under severe operating conditions.
- Protects vehicle emission systems.
- Delivers optimum fuel economy.

RECOMMENDED APPLICATIONS:

ILSAC GF-6A & API Service Category Resource Conserving SP (API License number 3233)

- Chrysler; MS-6395 (Revision S)
- Ford WSS-M2C946B-1 (5W-30)
- General Motors dexos1™ Gen 2 (License numbers 0W-20D10645HI161 & 5W-30D10646HI161)
- Backward compatible and supersedes General Motors GM-LL-A-025, GM4718M & GM6094M (obsolete)

Typical Characteristics			
Property	Method		
SAE Grade		0W-20	5W-30
General Motors Performance		dexos1	dexos1
Viscosity, cSt @ 40C	D-445	44.8	63.9
Viscosity, cSt @ 100C	D-445	8.4	11
Viscosity Index	D-2270	169	167
Specific Gravity, @60F	D-1250	0.846	0.849
Flash Point, COC (F)	D-92	230 (446)	232 (450)
Pour Point, C (F)	D-97	-42 (-44)	-39 (-38)
CCS, cP, maximum @ -30C	D-5293	5600 (-35C)	4900
NOACK Volatility @ 700 F, % loss	D-5800	<13	<13
Total Base Number (TBN)	D-2896	8.5	8.5
Sulfated Ash, wt. %	D-4929	0.90	0.90